

FROST

Fighters

PORTABLE HEATERS



**INDIRECT
FIRED**



**DIRECT
FIRED**





Temporary Heating Equipment
Since 1965



1500 Notre Dame
Winnipeg, MB R3E 0P9
TOLL FREE: 1 888 792 0374
DIRECT: (204) 775 8252
FAX: (204) 783 6794
WEB: www.frost-fighter.com
CORPORATE: www.ice-ww.com

Indirect Fired

OIL

	IDF 200 - OIL	IDF 350 - OIL	IDF 500 - OIL
MAX CAPACITY	210,000 BTU	350,000 BTU	500,000 BTU
HEATED AIR	2,500 CFM	2,800 CFM	3,100 CFM
DISCHARGE TEMP. *	150°F	200°F	220°F
WEIGHT	405 lbs	520 lbs	520 lbs
APPROVED	ETL	CSA	CSA
SHIPPING DIMENSIONS CRATED (LXWXH)	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"

PROPANE / NATURAL GAS

	IDF 200 - LP/NG	IDF 350 - LP/NG	IDF 500 - LP/NG
MAX CAPACITY	210,000 BTU	350,000 BTU	450,000 BTU
HEATED AIR	2,500 CFM	2,500 CFM	3,100 CFM
DISCHARGE TEMP. *	150°F	200°F	210°F
WEIGHT	405 lbs	520 lbs	520 lbs
APPROVED	ETL	ETL	ETL
SHIPPING DIMENSIONS CRATED (LXWXH)	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"

* Discharge Temp. (@50°F ambient)

Direct Fired

PROPANE / NATURAL GAS

	DF400	DF1500
CAPACITY	400,000 BTU	1,500,000 BTU/HI FIRE 800,000 BTU/LOW FIRE
FUEL	Vapor Propane/Natural Gas	Vapor Propane/Natural Gas
MANIFOLD PRESSURE	Propane 1.4" w.c. Natural Gas 3.5" w.c.	Propane 1.5" w.c. Natural Gas 3.6" w.c.
INLET PIPE CONNECTION	157 CFH/LP 4.35 US Gal/HR 390 CFH/NG 10.7 US Gal/HR	589 CFH/16.5 US Gal/HR-LP 1461 CFH/40.8 US Gal/HR-NG
GAS CONSUMPTION	3/4" NPT	1.25" NPT
ELECTRICAL REQUIREMENTS	120 Volts 15 Amps Circuit	120 Volts 20 Amp Circuit
FAN	2500 CFM 1/2 HP, 16" Diameter	7700 CFM 1 HP, 24" Diameter
SHIPPING DIMENSIONS CRATED (LXWXH)	51" x 30.5" x 33"	74.25" x 39.5" x 52.5"
WEIGHT	206 lbs	415 lbs
APPROVED	ETL	ETL