



KX057-4



SPECIFICATIONS

Specifications

Model				KX057-4		KX057-4 Angle Blade		
Type of ROPS / FOPS				Canopy / Cab				
Type of tracks				Rubber		Rubber / Steel		
Engine	Model			Kubota V2607-D1				
	Output (SAEJ 1995 gross)		HP (kW)/rpm	47.6 (35.5) / 2200				
	Output (SAEJ 1349 net)		HP (kW)/rpm	45.4 (33.8) / 2200				
	Displacement		cu.in. (cc)	159.6 (2615)				
Dimensions	Overall length		ft.in. (mm)	18'1.3" (5520)				
	Overall height		ft.in. (mm)	8'4.4" (2550)				
	Overall width		ft.in. (mm)	6'5.2"(1960)				
	Min. ground clearance		in. (mm)	1'0.2"(310)				
Hydraulic system	Pump capacity		gpm. (ℓ /min)	14.8 (56.1) Variable x 2 / 9.8 (37.0) Gear x 1				
	Auxiliary hydraulic flow	AUX1 / AUX2	gpm. (ℓ /min)	19.8 (75) / 9.8 (37)				
	Max. breakout force	Bucket / Arm	lbs. (kgf)	11177 (5070) / 5644 (2560)				
Drive system	Travel speed	Low / High	mph (km/h)	1.8 / 3.1 (2.8 / 4.9)				
	Max. traction force	Low speed	lbs. (kgf)	14480 (6567)				
	Tumbler distance		ft.in. (mm)	6'6.3" (1990)				
	Crawler length		ft.in. (mm)	8'2.4" (2500)				
	Shoe width	Rubber / Steel	ft. in. (mm)	1'3.7" (400)				
	Ground contact pressure	Rubber	Canopy / Cab	psi (kgf/cm ²)	4.52 (0.318) / 4.59 (0.323)		4.67 (0.329) / 4.75 (0.334)	
		Steel	Canopy / Cab	psi (kgf/cm ²)	-		4.76 (0.335) / 4.83 (0.340)	
Swing system	Unit swing speed		rpm	9.3				
	Boom swing angle	Left / Right	degree	70 / 55				
Blade	Dimensions	Width	ft. in. (mm)	6'5.2"(1960)				
		Height	ft. in. (mm)	1'4.1" (410)		1'4.7" (425)		
	Max. lift above ground	in. (mm)		17.3" (440)		20.0" (510)		
	Max. drop below ground		in. (mm)	16.1" (410)		18.3" (465)		
	Angle	Left / Right	degree	-		25		
Hydraulic oil (Reservoir/System)			gal (ℓ)	11.9 (45) / 20.9 (79)				
Fuel reservoir			gal (ℓ)	19.8 (75)				
Operating weight		Rubber	Canopy / Cab	lbs. (kgf)	12150 (5510) / 12345 (5600)		12565 (5700) / 12765 (5790)	
(Including operator's weight @ 175 lbs.)		Steel	Canopy / Cab	lbs. (kgf)	-		12790 (5800) / 12985 (5890)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt for almost all applications.

DIMENSIONS

